

Controlling Exposures to prevent occupational lung disease in the construction industry



HAZARDS AND RISKS

The main respiratory hazard associated with plastering activities is exposure to airborne plaster dust when mixing the material from a dry state to wet in preparation for use, and during sanding down of dried materials. This is because plastering materials contain composites, such as calcium sulphate hemihydrate, limestone and clays, small amounts of silica and mica, and sometimes hydrated lime. Inhalation of dust from these materials can lead to respiratory complaints and potentially serious diseases in the long term. Inadvertent disturbance of asbestos containing materials (ACMs) is also a risk.

Airborne dusts

Plaster dust (bagged material)

The long term health effects of regularly inhaling plaster dusts during mixing are unclear at present but likely to include chronic obstructive pulmonary disease (COPD – see below).

Inhaling dust from sanding of plaster materials

Can lead to occupational asthma and COPD, which includes serious conditions such as chronic bronchitis and emphysema, which is irreversible.

Silico

Inhaling fine silica dust, known as respirable crystalline silica (RCS) can also lead to serious lung diseases, including fibrosis, silicosis, COPD and lung cancer. These diseases can cause permanent disability and early death.

Asbestos

Plasterers can be at risk of exposure to asbestos from preparation of surfaces such as textured coverings (especially when sanding or grinding tools are used) and disturbing asbestos containing materials (ACMs), particularly when working in buildings built before 2000. Asbestos is classified as a category 1 carcinogen. Inhalation of airborne asbestos fibres can cause mesothelioma, asbestos-related lung cancer, asbestosis, and pleural thickening - which are fatal, serious and incurable diseases that can take many years to develop.

CONTROL OPTIONS

Elimination/prevention

Asbestos

• The aim is to avoid exposure completely. Information on the presence of asbestos should come from the premises' asbestos management plan and asbestos register. For information on work tasks involving asbestos and how to safely carry them out, refer to the applicable OH&S regulations. (e.g. requirements for employers to notify the relevant regulatory enforcing authority, designate areas where the work is being done, ensure medical examinations take place, maintain health records, etc.)

Engineering controls

- Use general mechanical ventilation to prevent accumulation of airborne dust and transfer dusts to outside.
- Use powered sanding tools with integrated, or "on-tool", dust extraction.

Safe working methods

- Work in a well ventilated area, ensuring good natural ventilation that allows dusts to readily disperse.
- Use hand tools in place of power tools, if feasible, for sanding tasks.
- Limit the number of persons near dusty work.
- Rotate workers undertaking dusty tasks.

PPF

- Respiratory protective equipment (RPE) should be used to supplement the above controls where necessary.
- RPE should be selected in accordance with CSA Z94.4-11 Selection, Use and Care of Respirators.
- Tight fitting RPE users should be subject to face fit tests to ensure the RPE affords each individual the anticipated level of protection.

MANAGING THE RISK

Training & communication, supervision, maintenance & testing of controls and air monitoring* are all vital aspects of managing the risk, in addition to health surveillance which can be a requirement in certain circumstances.

See our introductory Respiratory Health Hazards in Construction Fact Sheet Series: **Overview** for more information about what things to consider and implement.

Air monitoring

Air monitoring is a specialist activity. It may be needed as part of an exposure risk assessment, as a periodic check on control effectiveness and to assess compliance with relevant occupational exposure limits, or where there has been a failure in a control (for example if a worker reports respiratory symptoms).

A qualified occupational hygienist or occupational hygiene technologist can ensure exposure monitoring it is carried out in a way that provides meaningful and helpful results.